

POWER-LAN

Strømpanel 8 x 230V + J + 230 + J plug
10A sort 19" transient besk



Anvendelse

Monteres i 19" krydsfelt skabe. Panelet består af 8 stk. 230 V + J udtag samt 1,90 mtr. kabel med påmonteret stikprop. Panelet er forsynet med en transientbeskyttelse, som forhindrer transienter (lyn) at blive videreført til aktivt udstyr. Glimlampe, der indikerer at panelet får tilført strøm.

Specifikation

Bredde: 19"

Højde: 1HE

Antal udtag: 8 stk 220V + J

kabel: 1,90 m 3 x 1,50 mm²

Plug: 2 x 230 + J

Materiale udtag: Plast

Materiale hus: Sort metal

Strømpanel 8 x 230V + J + 230 + J plug 10A sort 19" transient besk

No.	Item	Detailed Description	
1	Product Series	AUE2250	
2	Socket Type	DK 1-3A Danmark socket[8];	
3	Socket Quantity	8	
4	Power Input	Left end single input	
5	Bracket Install	Frontal installation	
6	Cable with plug	DK 1-3a Denmark plug	
7	Control Function	Single power indicator	
8	Protection Function	No protecting function	
9	Case	Black	
10	Cable Specification	3 x 1.5 mm ² x 2M	
11	Product Size	L x W x H = 485.5 x 44.4 x 44.4 mm	
12	Mounting Length	484.5 mm	
13	Case Length	432.5 mm	
14	PDU Exponent	0,978	
15	Fittings	2pcs ϕ 6x16mm cross bolt, 2pcs M6 float nut	
16	Product Label	Product Name	Designated Power Distribution Unit for Cabinet
		Specification Model	AUE2250K1-08AHSNHB
		Rating voltage	250VAC 50/60Hz
		Rating Current	10A
		Max. Current	
		Max. Power	2500W
		Safety Authentication	CE
		Logo	RoHS
Producer			
No.	Add-In		
1	Socket assemble	No	
2	Interior Connection Wire	1.5 mm ² (16AWG)	
3	Interior Connection Style	Standard connection	
4	Fix the Cable	Small cable clamp	
5	Module Assemble (from left to right)	Pls refer to attatched drawing	