

Accessories

Network Interfaces



265357

Pack	Cat. Nos.	Network interface CS102
		<p>Network interfaces for UPS management via LAN or Wi-Fi connection.</p> <p>The Wi-Fi dongle allows the UPS to be connected to the data network without additional cables. The network interfaces CS102 is able to continuously control the UPS operations and handle multiple events (power failure, overload, bypass, anomaly, etc.) and consequently to carry out a series of actions, such as, for instance:</p> <ul style="list-style-type: none"> - Saving of event logs complete with date and time - Saving of main operating data trends complete with date and time - Sending of emails - Display of pop-up messages, shutdown operations and custom commands on remote computers (it is necessary that the CS102 shutdown client software agent is installed on these computers) - Switching ON and OFF the UPS - Sending of "Wake on LAN (WOL)" signals - SNMP protocol support - Sending of SNMP trap messages - Data display and configuration via internet browser - Firmware downloadable free of charge from the Internet - 10/100Mbit Base-T Ethernet connection (half-duplex and full-duplex) with self-recognition function - DHCP function <p>The card is housed in a dedicated UPS slot. Compatible with Daker DK Plus, Keor SPE, Keor S, Keor LP, Keor Line RT, Keor T, Keor T Evo, Keor Compact</p>
1	3 110 58	CS102 Network interface

MODBUS over IP
 HTTP/HTTps
 Program execution
 SNMP, SNMP Trap management
 Sending e-mails (SMTP)
 Log file, historical data file
 Performing computer shutdown

LIST OF OPERATING SYSTEMS SUPPORTED BY THE SOFTWARE

- Linux
- Windows