

LAN-OPTIC

Fusions splidser core alignment



Anvendelse

Digital Fusions splidser med automatisk fokus funktion.
Avanceret automatisk Core Alignment funktion, både X- og Y-akse display.
9 sekunders splidsetid
Autotjek af de cleavede fiberender

Features

- 9s quick splidsning
- Core alignment
- 4800mAh lithium battery
- 400X forstørrelse
- 3.5" farve LCD skærm
- Universal fiberholder (for ren fiber, patch kabler og pigtail)

Varenr.: 291008
EANnr.: 5706682028694

LAN-OPTIC

Fusions splicer core alignment

Specifications

Item	SH-A87S Fusion Splicer
Applicable Fiber Type	SM,MM,DS,NZDS
Applicable Fiber Count	Single
Applicable Fiber Diameter	Cladding diameter: 80~150um, coating diameter 100 ~ 1000um
Splice Mode	Stored 40 groups, 80 groups of user-defined
Average Splice Loss	0.02dB(SM),0.01dB(MM),0.04dB(DS),0.04dB(NZDS)
Return Loss	More than 60dB
Typical Splicing Time	9 sec(Typical time)
Typical Heating Time	26s(configurable heating time and adjustable heating time)
Fiber Holder	Multifunctional fiber holder(bare fiber, patch cords, pigtail and indoor cable)
Tensile test	2N
Screen	3.5 in. color LCD
Splicing Mode	17 groups
Heating Mode	9 groups
Optical Magnification	X, or Y: 400 times
Power Supply	11.1V lithium battery, 13.5V/5A power adapter, 12V vehicle power supply
Battery	Typical Operating 200 (splice / heat shrink)
Maximum storage	10000 set of the latest record storage
Power Saving	15% of the power of the lithium battery can be saved in a typical environment
Data interface	USB2.0
Operating environment	Altitude 0 ~ 4000m, 0 to 95% relative humidity, temperature -10 ~ 50degree, the maximum wind speed 15m/s
Storage Conditions	0 to 95% relative humidity, -40 ~ 80°C (except battery), -10 ~ 30°C (battery)
Weight	1.21kg (without battery), 1.5kg (including battery), including attachments packing gross weight: 5.1Kg
Size	214*136*110mm (fusion splicer) 330*183*214mm(plastic box)
Lighting	Convenient for the fiber installation in the evening
Packing	New waterproof, drop, more than can be heavy 300KG

LAN-OPTIC

Fusions splidser core alignment

Packing List

Main Unit		1pcs
Fiber Cleaver		1pcs
Indoor Cable Stripper		1pcs
CFS-3 Fiber Stripper		1pcs
Spare Electrodes		1 pair
Brush		1 pcs
Cooler		1pcs
Tweezers		1pcs
Hanging Fiber Reel		1pcs
Alcohol Bottle		1pcs
Fiber Holders	Universal Fiber Holders (bare fiber, patch cords, pigtail, indoor cable)	
Carrying Suitcase		1pcs
AC Adaptor		1pcs
Blower (dustproof)		1pcs
Manual		1pcs
Warranty/Certificate/List		1pcs