



COUPLER SUPERSOL PLUS IAS

Connection coupler for rigid and pliable conduits for concealed type installations

Connection coupler SUPERSOL PLUS is designed in such a way that is connected safely with the KOUVIDIS 3layer conduits [SUPERSOL PLUS](#), [SUPERFLEX PLUS](#) and [DUROFLEX PLUS](#), providing at least IP65 ingress protection. It is produced from specially stabilized thermoplastic PE

Coupler SUPERSOL PLUS has an inner termination lip which secures the correct and watertight connection of the conduit systems in concealed type installations.

APPLICATION FIELD

It is ideal for concealed type installations such as the underplaster, dry wall, chipboard, sub-ceiling and sub-floor.

| | |
|------------------------------|--|
| APPLICATION STANDARD: | EN 61386.1, EN 50642 |
| INSTRUCTIONS FOR COMPLIANCE: | 2014/35/EE (LVD), 2011/65/EE (RoHS) |
| COLOR: | RAL 7035 Light grey |
| TIGHTNESS DEGREES: | min IP 65 |





Properties

| | |
|---------------------------------|--|
| Raw material | Halogen free, heavy metals free (RoHS) and specially stabilized thermoplastic PE |
| Temperature range | -15°C to +105°C |
| Ingress protection | min IP65 |
| Electrical characteristics | With electrical insulated characteristics |
| Resistance to flame propagating | Non flame propagating |
| Halogen free | No toxic or corrosive gases in case of fire |
| Antistatic Technology | Protection against static electricity |