



COUPLER SUPERSOL PLUS IAS

Connection coupler for rigid and pliable conduits for concealed type installations

Connection coupler SUPERSOL PLUS is designed in such a way that is connected safely with the KOUVIDIS 3layer conduits [SUPERSOL PLUS](#), [SUPERFLEX PLUS](#) and [DUROFLEX PLUS](#), providing at least IP65 ingress protection. It is produced from specially stabilized thermoplastic PE and is offered in yellow color RAL 1023.

Coupler SUPERSOL PLUS has an inner termination lip which secures the correct and watertight connection of the conduit systems in concealed type installations.

APPLICATION FIELD

It is ideal for concealed type installations such as the underplaster, dry wall, chipboard, sub-ceiling and sub-floor.

APPLICATION STANDARD:	EN 61386.1, EN 50642
INSTRUCTIONS FOR COMPLIANCE:	2014/35/EE (LVD), 2011/65/EE (RoHS)
COLOR:	YELLOW RAL 1023
TIGHTNESS DEGREES:	min IP 65





Properties

Raw material	Halogen free, heavy metals free (RoHS) and specially stabilized thermoplastic PE
Temperature range	-15°C to +105°C
Ingress protection	min IP65
Electrical characteristics	With electrical insulated characteristics
Resistance to flame propagating	Non flame propagating
Halogen free	No toxic or corrosive gases in case of fire
Antistatic Technology	Protection against static electricity