



## CONDUR IAS

### Connection coupler of pliable and rigid conduits

CONDUR coupler is safely connected with KOUVIDIS rigid and pliable conduits, ensuring minimum Ingress Protection IP65. It's a part of CONDUR – CONFLEX, MEDISOL – MEDIFLEX, SILCOR – SIFLEX, CONDUR HF – CONFLEX HF and MEDISOL HF – MEDIFLEX HF conduit systems for cable management and protection.

CONDUR coupler incorporates a special anti – rodent additive to maximize safety in electrical installations from animal attacks. (Patent Protected by European Patent Office).

Ideal for exposed electrical installations.

---

APPLICATION STANDARD:	<b>EN 61386.1, EN 50642</b>
INSTRUCTIONS FOR COMPLIANCE:	<b>2014/35/EU (LVD), 2011/65/EU (RoHS)</b>
COLOR:	<b>RAL 7035 Light grey</b>
TIGHTNESS DEGREES:	<b>min IP 65</b>

---





## Properties

Raw material	Halogen free, heavy metals free (RoHS) and specially stabilized thermoplastic PE
Temperature range	-25°C to +120°C
Ingress protection	min IP65
Electrical characteristics	With electrical insulated characteristics
Resistance to flame propagating	Non flame propagating
Ageing resistance	UV stabilized
Halogen free	No toxic or corrosive gases in case of fire
Antistatic technology	Protection against static electricity