

POWER-LAN

Strømpanel 8 x SHUKO + SHUKO plug 3m ledning
230V 16A 19" Transientbeskyttet



Anvendelse

For montage i 19" rack skabe.
Panelet består af 8 stk. vinklet SHUKO 230V udtag,
16A SHUKO plug samt 3 mtr. kabel med påmonteret stikprop.
Panelet er forsynet med transientbeskyttelse og glimlampe, der
indikerer, at panelet får tilført strøm.

Varenr.: 261888
EANnr.: 5706683027222

Specifikation

Bredde: 19"

Højde: 1HE

Antal udtag: 8 stk. SHUKO 230V

Kabel: 3mtr. 3 x 1,5mm²

Plug: 16A SHUKO

Materiale udtag: Plast

Materiale hus: Sort metal

POWER-LAN

19" Transientbeskyttet Strømpanel 8 x SHUKO + SHUKO plug 3m ledning 230V 16A

PDU Technology Specification

Date: 02/01/2023

NO.: 001

Customer	LAN-COM	RoHS	Yes
Product Name	Designated Power Distribution Unit for Cabinet	Customer's Code	
Part Number	AUE2250D3-08AHDNHB	Picture Code	
No.	Item	Detailed Description	
1	Product Series	AUE2250	
2	Socket Type	DIN49440 16A Socket [8];	
3	Socket Quantity	8	
4	Power Input	Left end single input	
5	Bracket Install	Frontal installation	
6	Cable with plug	16A DIN49441 plug	
7	Control Function	No controlling function	
8	Protection Function	Removable AU-EC A20-C2 surge protection component[1];	
9	Case	Black	
10	Cable Specification	3 x 1.5 mm ² x 3M	
11	Product Size	L x W x H = 490 x 60 x 44.4 mm	
12	Mounting Length	459 mm	
13	Case Length	437 mm	
14	PDU Exponent	0.978	
15	Fittings	4pcs φ6×16mm cross bolt, 4pcs M6 float nut	
16	Product Label	Product Name	Designated Power Distribution Unit for Cabinet
		Specification Model	
		Rating voltage	250VAC 50/60Hz
		Rating Current	16A
		Max. Current	
		Max. Power	4000W
		Safety Authentication	CE
		Logo	RoHS
	Producer		
No.	Add-In		
1	Socket assemble	No	
2	Interior Connection Wire	2.5 mm ² (14AWG)	
3	Interior Connection Style	Standard connection	
4	Fix the Cable	Small cable clamp	
5	Module Assemble (from left to right)	Pls refer to attached drawing	
6	Others	No	

POWER-LAN

19" Transientbeskyttet Strømpanel
8 x SHUKO + SHUKO plug 3m ledning 230V 16A

